

## DESCRIPTION

Causeway Kenlux Synthetic Enamel is specially formulated and designed for all interior and exterior timber and metal applications where a gloss finish is desired. Kenlux Synthetic Enamel has high coverage, excellent opacity and is fast drying.

- Excellent Washability
- Excellent Coverage
- Self-levelling Properties
- High Gloss

## TYPICAL USES

- Decorative paints with a wide colour range for coatings on wood, walls and steel gates.
- Also suitable for coatings on steelworks, pipelines and concrete.

## APPLICATION

- Apply over primed surfaces
- Method of application
  - Conventional Spray
  - Brush

## SURFACE PREPARATION

Recommended Primer

- **Wood:** Aluminium Wood & Metal Primer
- **Metal:** Anti-Corrosive Primer/ Zinc Phosphate Primer
- **Galvanized Steel & Aluminium:** Etch Primer
- **Masonry:** Alkaline resisting wall primer
- **Plastic:** Plastic primer

## APPLICATION INSTRUCTIONS

- Ensure that the correctly primed substrate is clear of any dust, oil, and other contaminants before applying the paint.
- Apply a layer of recommended undercoat and leave overnight before applying the topcoat.
- Dilute the paint to the required viscosity, depending on the type of application method employed.

## HEALTH & SAFETY

Always keep paint out of reach of children. Ensure good ventilation during application and drying. Do not smoke while painting. Highly flammable. Store in a cool dry place away from heat and sparks.



## TECHNICAL DATA SHEET KENLUX ENAMEL

### TECHNICAL DATA

- COLOR : Standard Colours
- COMPONENTS : Single
- FINISH : High Gloss, Semi-gloss & Matt
- CURING MECHANISM : Oxidation process
- VISCOSITY : 150 sec Ford cup 4
- SPECIFIC GRAVITY : ~ 1.10
- VOLUME OF SOLIDS : Approximately 50%
- THINNER : Causeway Turpentine
- MIXING RATIO : 25% (Brush) / 40% (Spray)
- SPRAY VISCOSITY : 15 sec (Ford 4)
- RECOMMENDED : 25µm THICKNESS PER COAT
- THEORETICAL : ~ 15-16m<sup>2</sup>/L (Based on COVERAGE 25µm DFT)
- DRYING TIME : 4 hours (Touch dry)  
16 hours (Hard dry)
- RE-COATING INTERVAL : 16 hours
- POT LIFE : N/A
- SHELF LIFE : Best before 24 months

### PACKING

- 200 ml
- 500 ml
- 1 Litre
- 4 Litres