

DESCRIPTION

Causeway Kenlux Anti-Corrosive paint is an alkyd based synthetic paint for protection against corrosion for all types of metal surfaces. It is ideal to be used as a primer before application of Enamel paint.

- Good Adhesion.
- Anti-rust Properties.
- Excellent base for Subsequent Coatings.

TYPICAL USES

- Act as a primer or anti-corrosive coating for ferrous metals.
- Also recommended as undercoat for wood.

APPLICATION

- Method of application
- Conventional Spray
 - Brush
 - Airless Spray

APPLICATION INSTRUCTIONS

- Ensure that the substrate is free of rust, oil, grease and other contaminants prior to any painting work.
- Dilute the paint to the required viscosity, depending on the type of application method employed.

HEALTH & SAFETY

Always keep paint out of reach of children. Ensure good ventilation during application and drying. Do not smoke while painting. Highly flammable. Store in a cool dry place away from heat and sparks.



TECHNICAL DATA SHEET **KENLUX ANTI CORROSIVE PAINT**

TECHNICAL DATA

○ COLOR	: Red, Grey, Brown, Green & Black
○ COMPONENTS	: Single
○ FINISH	: Semi-gloss
○ CURING MECHANISM	: Oxidation process
○ VISCOSITY	: 150 sec (Ford 4)
○ SPECIFIC GRAVITY	: ~ 1.30 +/- 0.10
○ VOLUME OF SOLIDS	: Approx 55%
○ THINNER	: Causeway Turpentine Causeway Thinner
○ MIXING RATIO	: 25% (Brush) / 40% (Spray)
○ SPRAY VISCOSITY	: 15 sec (Ford 4)
○ RECOMMENDED THICKNESS PER COAT	: 25-35µm
○ THEORETICAL COVERAGE	: ~ 10-12m ² /L (Based on 25-30µm DFT)
○ DRYING TIME	: 45 minutes (Touch dry) 16 hours (Hard dry)
○ RE-COATING INTERVAL	: 08 hours
○ POT LIFE	: N/A
○ SHELF LIFE	: Best before 24 months

PACKING

○ 200 ml ○ 500 ml ○ 1 Litre ○ 4 Litres