

TECHNICAL DATA SHEET

CAUSEWAY KENLUX FLOOR PAINT

DESCRIPTION

- Good adhesion with modified alkyd resin based decorative coating.
- Good applicability.
- Good abrasion & scuff resistance.
- Quick drying.
- Excellent wash ability.
- Excellent color resistance.
- High opacity for good coverage.

TYPICAL USES

- On properly prepared horizontal masonry, wood & metal surfaces.

APPLICATION

- Apply over primed surfaces
- Method of application

- * Roller
- * Brush
- * Spray

APPLICATION INSTRUCTIONS

- Ensure that the substrate is clear of any dust, oil, grease and other contaminants before applying the paint.
- Dilute the paint to the required viscosity, depending on the type of application method employed.

HEALTH & SAFETY

Always keep paint out of reach of children. Ensure good ventilation during application and drying. Do not smoke while painting. Highly flammable. Store in a cool dry place away from heat and sparks.

TECHNICAL DATA

➤ COLOR	:Green, Black, Red, Brown & grey
➤ COMPONENTS	:Single
➤ FINISH	:Semi-gloss/Gloss
➤ CURING MECHANISM	:Air dry
➤ VISCOSITY	:75sec (Ford 4)
➤ SPECIFIC GRAVITY	: ~ 1.350
➤ VOLUME OF SOLIDS	: Approx. 52%
➤ THINNER	:Causeway Thinner
➤ MIXING RATIO	:Depending on the Requirement (10% max.)
➤ SPRAY VISCOSITY	:N/A
➤ RECOMMENDED THICKNESS PER COAT	:40um
➤ THEORETICAL COVERAGE	: ~ 10m ² /L (based on 40um DFT)
➤ DRYING TIME	: ~ 2 hours (Touch dry) 16 hours (Hard dry)
➤ RE-COATING INTERVAL	:16 hours
➤ POT LIFE	:n/a
➤ SHELF LIFE	:best before 24 months

PACKING

- 200ml
- 500ml
- 1Litre
- 4Litres