

DESCRIPTION

Causeway Luxury Shield is an advanced all acrylic all weather protection UV resistant exterior emulsion, It is specially formulated using UV resistant pigments which is proven for at least 5 years from algae, fungus, cracking, peeling, fading and dirt pickup. Causeway Luxury Shield is SLS 557 & Green certified

FEATURES

- High performance acrylic
- UV resistance with Excellent colour retention
- Crack and peel resistant
- Superior Hiding Power
- High Washability
- No added lead or mercury
- Low VOC
- Anti-fungus & Algae resistant
- Fast drying, Excellent Adhesion
- All-weather protection

TYPICAL USES

For the decoration and protection of Exterior building surface

- Asbestos
- Cement
- Masonry
- Plaster
- Brickworks Hard & Soft Boards

APPLICATION

- Apply over primed surfaces
- Method of Application
 - Roller
 - Brush
 - Spray

SURFACE PREPERATION

- Surface must be clear, dry and sound.

APPLICATION INSTRUCTIONS

- Dilute with fresh water and it should not exceed 30% by using fresh water.

1st Coat : 25% - 30% of Water

2nd Coat : 20% - 25% of Water



TECHNICAL DATA SHEET **CAUSEWAY LUXURY SHIELD**



TECHNICAL DATA

- COLOR : Most colours achievable
- COMPONENTS : Single
- FINISH : Low sheen
- CURING MECHANISM : Air dry
- VISCOSITY : 45 ± 5P at 30°C
- SPECIFIC GRAVITY : 1.50gml - 1.4gml⁻¹
- VOLUME OF SOLID : 50%
- VOC Content : Not Detected
- RECOMMENDED THICKNESS PER COAT : 25 - 35 microns
- THEORETICAL COVERAGE : 15m² / Ltr (Base on 30 Microns / coat)
- NO OF COATS : 2 to 3 coats depends on requirement
- RE-COATING INTERVAL : Min 2 hours at 30°C
- POT LIFE : N/A
- SHELF LIFE : Best before 24 months

PACKING

- 1 Litre
- 4 Litres
- 10 Litres
- 20 Litres