

## **DESCRIPTION**

Causeway Water Base Exterior Acrylic Wall Filler Primer is a high quality primer with excellent durability. It has to be applied prior to the application of exterior emulsion. it exhibits good alkali, fungus and algae resistance.

An Pure Acrylic Co-polymer Emulsion base primer

- Excellent Algae and Fungus resistance
- Excellent Durability
- Excellent Adhesion
- Scrub Resistance
- Easy Application
- Elongation properties

## **TYPICAL USES**

An undercoat to accommodate the movement of hairline cracks. It is a low PVC product so that the small particle size of emulsion can easily flow and transfer into the small tiny holes on the concrete to stop the alkaline from coming out.

- Asbestos
- Cement
- Masonry
- Plaster
- Brickworks Hard & Soft Boards

## **APPLICATION**

Ensure that the surface is free from dust and other contamination. Wash the surface with high pressure cleaner if necessary.

- Method of Application
  - Roller
  - Brush

## **SURFACE PREPARATION**

- Surface must be clear, dry and sound.

## **APPLICATION INSTRUCTIONS**

- Product is ready for use. If thinning necessary, it should not exceed 30% by using fresh water.



## **TECHNICAL DATA SHEET**

### **CAUSEWAY ACRYLIC EXTERIOR WALL FILLER PRIMER (PREMIUM QUALITY)**

#### **TECHNICAL DATA**

- COLOR : White
- COMPONENTS : Single
- FINISH : Smooth satin
- CURING MECHNISM : Air dry
- VISCOSITY : 40 P at 30<sup>0</sup>C
- SPECIFIC GRAVITY : 1.3g / ml
- THEORETICAL COVERAGE : 12 - 15m<sup>2</sup> (Base on 35 microns DFT)
- RE-COATING INTERVAL : Min 2 - 3 hour at 25<sup>0</sup>C
- Dry time : Surface Dry : 15 minutes  
Hard Dry : 16 hours
- POT LIFE : N/A
- SHELF LIFE : Best before 24 months

#### **PACKING**

- 4 Litres
- 10 Litres
- 20 Litres